



Pre-installation Data Sheet

Bathtubs and Whirltubs

Index

Notes.....	2
Pre-installation	3
Maintenance openings	5
Data sheets for bathtubs and whirltubs	9

Notes

PLANNING

Before starting the installation, plan the layout in detail, taking the site conditions into consideration.

TARGET READERSHIP AND QUALIFICATIONS

All work associated with the installation and water connection may only be undertaken by a plumber and all work associated with the electrical installation may only be undertaken by a licensed electrician.

SAFETY INSTRUCTIONS

Incorrect handling/transport may result in product damage.

The metal frame and whirl system are not resilient.

- > Never hold by the metal frame or whirl system.

Improper transport can cause damage to the product and/or property damage, e.g. leaks.

- > Wear appropriate protective clothing.
- > Avoid knocks.

Risk of product and/or property damage!

The breach of local and country-specific regulations and standards can cause damage to the product and/or property damage.

- > Observe the local installation regulations and any country-specific standards at all times.

Duravit AG assumes no liability for the consequences of improper handling or improper transport.

Pre-installation

INSTALLATION LOCATION / INSTALLATION ROOM

> Make sure that the installation location fulfils the following criteria

Doors / external access	Ensure that doors or other access openings are large enough to accommodate transport dimensions, keeping in mind the weight and need for sufficient manoeuvring room.
Required area	Allow for enough space around the tub for the installation.
Floor	- Completely level. - At a right angle to the wall. - Note the overall strength of the floor structure including the floor finish. - There must not be any underfloor heating under the tub. - Install tubs after the tiles. (Top edge of finished floor). - Depending on the combination of tub and whirl system it is possible that system components may protrude beyond the edge of the tub. We therefore recommend installation in a support frame. Tolerances for acrylic: As a result of the manufacturing process, deviations from the nominal dimensions may occur within the limits specified in the DIN 198 standard. Please take this into account in your planning.
Wall	- Tiled. - At a right angle to the tub. - Completely straight. - Note the overall strength of the wall structure including the wall finish.

WATER INSTALLATION

NOTE


Bathtubs without overflow will overflow into the room.

> If a bathtub is installed without an overflow, a floor drain must be installed to protect the building against overflow water in accordance with DIN 1986-100.

NOTE

A pipe interrupter is absolutely essential for tubs with a base inlet (DIN EN 1717).

> Comply with assembly scheme.



Water connection

- Connections for the water supply and drains must be in compliance with the currently valid standards and public regulations.
- Position the water drain (DN 50) flush to the mounting surface or out of the wall directly above the mounting surface; see drawing for recommended area.

MAINTENANCE OPENINGS AND AIR SUPPLY

NOTE

It is recommended to install the tub with a removable bathtub panel due to the improved maintenance options.

Tiling the tub

The following maintenance openings must be provided:

- Cable-driven waste and overflow 200 x 200 mm
 - Units 500 x 500 mm
- (Please see the section on "Maintenance openings")

- Provide an opening in the panel for the air supply with an effective area of approx. 15 cm² (e.g. 3 x 5 cm or 2 x 7.5 cm).

Tub with a panel

- The panel must be removed for maintenance, and with a seamless panel, the tub must be removed from the wall. Your plans should therefore include a clearance in front of the tub.
- The air supply for the whirl system (ventilation grille/ventilation slot) must not be covered.

ELECTRICAL INSTALLATION



DANGER

Risk of fatal electric shock

- Disconnect the power supply while working on the electrical components.
- The device must be earthed. Earthed appliances must be permanently connected to fixed wiring.
- Connect the device only to the designated electrical cable.
- NEVER touch the power supply line with wet hands.

Pre-installation

- Lay a permanent power supply line which must be on a separate circuit.
 - The device itself does not have electrical leakage protection function. The device must be supplied through a residual current device (RCD) with a rated residual operating current not exceeding 30 mA.
 - Means for disconnection must be incorporated in the fixed wiring in accordance with the wiring rules and have a contact separation in all poles that provides full disconnection under overvoltage category III conditions outside the prescribed protection zones (0 – 2).
 - Leave 3000 mm of the supply line exposed.
- Lay an equipotential bonding cable:
 - Leave 3000 mm of cable exposed.
- Select a supply line cross-section based on the connected load on the identification plate (2.5 mm – 4 mm).
- Confirm that the grounding wire is 10 mm (3/8") longer than the L and N wire.

> Install a circuit breaker.

76XXXX XX X XX XXX6:

220 – 240 V AC, 60 Hz


Fuse

$I_N = 16 \text{ A}$

RCD

$I_{\Delta N} \leq 30 \text{ mA}$

PROTECTION ZONES



* Or the height of the highest fixed-location shower head/water outlet, whichever is higher.

WHITE LED LIGHT UNDER THE EDGE OF THE TUB FOR BATHTUBS

Electrical data

Power supply

White LED light under the edge of the tub	220 – 240 V AC, 50/60 Hz,
#791847 00 0 00 0000	50 W
#791848 00 0 00 0000	
#791849 00 0 00 0000	

Fuse $I_N = 16 \text{ A}$

RCD

$I_{\Delta N} \leq 30 \text{ mA}$

WHIRLTUBS

Electrical data

Whirl system	Rated power with standard equipment	Max. rated power, fully-equipped
Air System (# 760XXX XX X AS 00XX)	0.76 kW	0.85 kW
Air System (DuraSolid) (# 760XXX XX X AS 00XX)	0.58 kW	0.58 kW
Jet Project (# 760XXX XX X JP 10XX)	0.66 kW	0.66 kW
Jet System (# 760XXX XX X JS 10XX)	0.59 kW	0.67 kW
Combi-System P (# 760XXX XX X CP 10XX)	1.89 kW	1.98 kW
Combi-System E (# 760XXX XX X CE 10XX)	1.91 kW	2.96 kW
Combi-System L (# 760XXX XX X CL 10XX)	1.59 kW	2.64 kW
Jet System E (# 760XXX XX X JE 10XX)	1.14 kW	2.20 kW

Power supply

76XXXX XX X XX XXX0:


220 – 240 V AC, 50 Hz

Maintenance openings


Maintenance

Install the whirltub in such a way that all of the important equipment (pump, blower and control system) remains accessible. It is recommended to install the tub with a removable furniture panel for easy maintenance.

Blue Moon




760143




760402


Cape Cod




760330



760362




760363




760364


Darling New




760242




760243




760244, # 760245



760246




760247




760248


D-Code




760095, # 760096,
760098, # 760100




760097, # 760099



760101



760137



760138


Location of the whirl system components

The illustrations show the standard configuration for the components of the whirl system* with the location of the operating unit. The back massage is located at the head end (depending on the whirl system).


Custom-made designs available on request. In such cases we will require a drawing showing the desired layout. Duravit will confirm whether the desired layout can be implemented.

* Please note that depending on the combination of tub and whirl system it is possible that system components may protrude beyond the edge of the tub. We therefore recommend installation in a support frame

D-Neo




760471, # 760472, # 760475,
760478, # 760479




760476


DuraSquare




760426



760427




760428, # 760429




760430


DuraStyle



760292, # 760294, # 760296




760293, # 760295, # 760297




760298


Happy D.2




760308, # 760310, # 760312



760309, # 760311, # 760313




760314, # 760315




760316

760317


Happy D.2 Plus




760449



760450




760451




760453


Luv



760431




760432




760433


Paiova




Starck




Vero Air



Vero



Legend




* Only Combi-Systems / ** The number of operating elements is based on the whirl system and the additional modules selected / *** Only necessary for Combi-System E/L in combination with sound and/or coloured LED light

Data sheets for bathtubs and whirltubs


Pre-installation DuraSquare # 7X0426

1800 x 800 x 485


Design by Duravit




- H** Hot water connection
- C** Cold water connection
- D** Drain connection
- MW1** Mixed water connection for waste and overflow with water inlet
- MW2** Mixed water connection for waste and overflow with base inlet
- EC** Electricity connection




Siphon for bathtub # 700426



Siphon with base inlet for bathtub # 700426



Siphon for whirltub # 760426



Siphon with base inlet for whirltub # 760426

	Height	including feet
X Bathtub	545	610
X Whirltub	545	610


Technical specifications

Net weight kg	Floor load kg/m2	Shipping weight kg	Shipping dimensions l x w x h (cm)	Water inlet OD, Base inlet OD	Whirlsystem	Model-No.
74,0	211	138,0	200 x 100 x 70	1/2", 3/4"		700426 00 0 00 0000
84,0	218	148,0	200 x 100 x 70	1/2", 3/4"	Air-System	760426 00 0 AS 0000


Pre-installation DuraSquare # 7X0427

1800 x 800 x 610


Design by Duravit




- H** Hot water connection
- C** Cold water connection
- D** Drain connection
- MW1** Mixed water connection for waste and overflow with water inlet
- MW2** Mixed water connection for waste and overflow with base inlet
- EC** Electricity connection




Siphon for bathtub # 700427



Siphon with base inlet for bathtub # 700427



Siphon for whirltub # 760427



Siphon with base inlet for whirltub # 760427


Technical specifications

Net weight kg	Floor load kg/m ²	Shipping weight kg	Shipping dimensions l x w x h (cm)	Water inlet OD, Base inlet OD	Whirlsystem	Model-No.
104,0	249	168,0	200 x 100 x 70	1/2", 3/4"		700427 00 0 00 0000
114,0	256	178,0	200 x 100 x 70	1/2", 3/4"	Air-System	760427 00 0 AS 0000


Pre-installation DuraSquare # 7X0428

1800 x 800 x 610


Design by Duravit




- H** Hot water connection
- C** Cold water connection
- D** Drain connection
- MW1** Mixed water connection for waste and overflow with water inlet
- MW2** Mixed water connection for waste and overflow with base inlet
- EC** Electricity connection




Siphon for bathtub # 700428



Siphon with base inlet for bathtub # 700428



Siphon for whirltub # 760428



Siphon with base inlet for whirltub # 760428


Technical specifications

Net weight kg	Floor load kg/m ²	Shipping weight kg	Shipping dimensions l x w x h (cm)	Water inlet OD, Base inlet OD	Whirlsystem	Model-No.
104,0	249	168,0	200 x 100 x 70	1/2", 3/4"		700428 00 0 00 0000
114,0	256	178,0	200 x 100 x 70	1/2", 3/4"	Air-System	760428 00 0 AS 0000


Pre-installation DuraSquare # 7X0429

1800 x 800 x 610


Design by Duravit




- H** Hot water connection
- C** Cold water connection
- D** Drain connection
- MW1** Mixed water connection for waste and overflow with water inlet
- MW2** Mixed water connection for waste and overflow with base inlet
- EC** Electricity connection




Siphon for bathtub # 700429



Siphon with base inlet for bathtub # 700429



Siphon for whirltub # 760429



Siphon with base inlet for whirltub # 760429



Technical specifications

Net weight kg	Floor load kg/m ²	Shipping weight kg	Shipping dimensions l x w x h (cm)	Water inlet OD, Base inlet OD	Whirlsystem	Model-No.
108,0	252	172,0	200 x 100 x 70	1/2", 3/4"		700429 00 0 00 0000
118,0	259	182,0	200 x 100 x 70	1/2", 3/4"	Air-System	760429 00 0 AS 0000

Pre-installation DuraSquare # 7X0430

1850 x 850 x 610

Design by Duravit



Siphon for bathtub # 700430

- H Hot water connection
- C Cold water connection
- D Drain connection
- EC Electricity connection

	Height	including panel
X Bathtub	485	610
X Whirltub	485	610



Technical specifications

Net weight kg	Floor load kg/m ²	Shipping weight kg	Shipping dimensions l x w x h (cm)	Whirlsystem	Model-No.
138,0	285	202,0	200 x 100 x 70		700430 00 0 00 0000
148,0	291	212,0	200 x 100 x 70	Air-System	760430 00 0 AS 0000

Pre-installation DuraSquare # 700460

1600 x 750 x 610

Design by Duravit



Siphon for bathtub # 700460

- H Hot water connection
- C Cold water connection
- D Drain connection
- EC Electricity connection

	Height	including panel
X Bathtub	485	610
X Whirltub		

Technical specifications

Net weight	Floor load	Shipping weight	Shipping dimensions	Whirlsystem	Model-No.
kg	kg/m ²	kg	l x w x h (cm)		
109,0	275	149,0	200 x 100 x 70		700460 00 0 00 0000

DURAVIT AG
P.O. Box 240
Werderstr. 36
78132 Hornberg
Germany
Phone +49 78 33 70 0
Fax +49 78 33 70 289
info@duravit.com
www.duravit.com

